

Pumpable Sludges

In advance of any delivery a detailed waste description in English or German has to be provided (safety data sheet, analysis and/or sample).

Delivery System

- Standard or vacuum tankers
- ASF containers
- Plastic IBC's

Technical Delivery Conditions

- The temperature of the waste must be below its ignition point
- The waste must be fully pumpable and drain from the container without assistance, sediment content < 30%
- The waste must not contain solid agglomerates or foreign bodies such as rags, wood, foil or similar bulk contamination
- Waste must not tend to flocculate, polymerise or to become viscous when temperature drops
- With ASF containers/plastic IBC's leave approx. 10% of container volume for expansion

Prior agreement must be obtained for deviation from the conditions mentioned above

Chemical/Physical Delivery Conditions

The limits for the parameters listed below are given in the relevant waste disposal quotation. If the values given are exceeded, SAVA must first be informed and surcharges for the relevant parameters calculated.

- Total chlorine
- Total sulphur
- Ash residue
- pH value
- Total fluorine, bromine and iodine
- Total cadmium and thallium
- Total sodium and potassium

- Mercury: < 10 mg/kg (If the initial limit for mercury is exceeded, SAVA must first be informed. A surcharge will automatically follow.)

Exclusion List

This covers materials which SAVA is not authorised to accept and those which, due to the potential risk, cannot be accepted in the pumpable sludge cassette: these are documented in Appendix 1.